



VST Range

INSULATED PLATFORMS



CAT C 46kV
INSULATED



7.5T MINIMUM
GVW



ARTICULATED
WITH TELESCOPIC
BOOM



MATERIAL
HANDLING
CAPABILITY



360°
CONTINUOUS
ROTATION



TYPE
APPROVED



EURO 6
COMPLIANCE

SPECIFICATIONS

	VST36MHi	VST40MHi	VST5000MHi	VST5500MHi	VST6000MHi
Working height*	13.4m	14.8m	17.2m	18.9m	20.3m
Platform height	11.4m	12.8m	15.2m	16.9m	18.3m
Max. outreach at:	8.3m	8.5m	11.7m	12.1m	12.5m
Articulated lower boom	0° to 80°	0° to 80°	0° to 80°	0° to 80°	0° to 80°
Main boom	-25° to 80°	-25° to 80°	-25° to 80°	-25° to 80°	-25° to 80°
Max. material handling	455kg	455kg	455kg	455kg	455kg
Bucket rotation	180°	180°	180°	180°	180°
Slew rotation	360°	360°	360°	360°	360°
	cont.	cont.	cont.	cont.	cont.
Electric insulation	Up to 46kV	Up to 46kV	Up to 46kV or optional 69kV	Up to 46kV or optional 69kV	Up to 46kV or optional 69kV

* Subject to mounting vehicle

Specifications are subject to vehicle and options fitted - please contact us for further information

STANDARD

- CAT C - 46kV insulated for live working (ANSI A92.2)
- Telescopic insulated platform
- Lower boom capable of 80° operation
- Full pressure hydraulic single lever upper controls
- A-frame outriggers to rear
- Aluminium flatbed
- Manual operated jib
- Emergency pump system
- Emergency stop at platform and pedestal
- Full functions at ground
- Torqued and sealed critical fasteners
- 4 x outrigger spreader pads with carrying frames
- Protective covers for insulated booms

OPTIONS

- 69kV insulation
- Material Handling (MH) jib and winch capability up to 455kg
- Hydraulic operated jib
- Radial outriggers to front*
- Bespoke aluminium toolboxes
- Bespoke fibreglass GRP lockers
- Earth grounding cable
- Thermostatically controlled locker heaters
- Hydraulic pressure intensifier
- Chapter 8 compliance

* Subject to platform type

As our insulated platforms can be configured and specified to customer requirements, please contact Versalift direct to discuss your particular situation and operation conditions.








VST40MHi mounted on a Unimog U423

The photographs in this brochure are for promotional purposes only. Specifications are subject to change without notice.

VST Range

INSULATED PLATFORMS



WORKING ENVELOPES



1 Altendiez Way,
Latimer Park,
Burton Latimer,
Kettering, NN15 5YT
T: 01536 721010
F: 01536 721111
E: sales@versalift.co.uk
W: www.versalift.co.uk



TRACK MOUNTED

PICK-UP MOUNTED

VAN MOUNTED

CHASSIS MOUNT

TRUCK MOUNTED

INSULATED PLATFORM