

VOE36IVIHi

INSULATED PLATFORM





CAT C 46kV INSULATED



MATERIAL HANDLING CAPABILITY



OVER CENTRE MODELS



TWIN 130KG SWL BUCKETS



360° CONTINUOUS ROTATION



TYPE APPROVED



SPECIFICATIONS


Working height*	13.3m
Platform height	11.3m
Max. outreach	9.3m
Max. outreach with material handling	7.3m
Max. bucket capacity (SWL)	2x130kg
Max. material handling (MH)	670kg
Min. GVW	12500kg
Bucket rotation	180°
Insulation rating to ANSI	A92.2 CAT C 46kV

Specifications are subject to vehicle and options fitted - please contact us for further information * Subject to mounting vehicle

STANDARD

- A-frame outriggers to rear, radial outriggers to front
- 2 x 130kg single operative buckets
- Jib and winch with 670kg materials handling lifting capability
- Jib pole with 120° arc
- Over centre boom geometry
- Lower boom insert
- 360° continuous rotation
- Full pressure hydraulic controls to bucket and pedestal
- Hydraulic tool outlet at operator's bucket
- Emergency stop at platform and pedestal
- Full functions at ground
- Full platform functionality on emergency power
- 4 x outrigger speader pads with carrying frames
- Protective covers for insulated boom parts
- Tree guards for bucket protection

VOE36MHi **METRES**



Working envelope at 2x130kg bucket SWL

/ERSALIFT


I Altendiez Way, Latimer Park, Burton Latimer, Kettering. NNI5 5YT T: 01536 721010 F: 01536 721111 E: sales@versalift.co.uk W: www.versalift.co.uk TRACK MOUNTED

OPTIONS

- H-frame outriggers to front
- Earth grounding cable
- Bespoke aluminium toolboxes
- Bespoke fibreglass GRP lockers
- Thermostatically controlled locker heaters
- Chapter 8 compliance

As our insulated platforms can be configured and specified to customer requirements, please contact Versalift direct to discuss your particular situation and operation conditions

Material Handler Capacity





Efficient operation of materials handler with twin bucket system

INSULATED PLATFORI

VOE36MH

Jib and winch provides up to 670kg lifting capability



Can work on live network up to 46kV CAT C



Improved stability with proven A-frame and radial outrigger system



Mounted on a Mercedes Unimog U423 Euro 6

The photographs in this brochure are for promotional purposes only. Specifications are subject to change without notice.













PICK-UP MOUNTED

VAN MOUNTED CHASSIS MOUNT TRUCK MOUNTED

INSULATED PLATFORM