VERSALIFT VERSALIFT VIL-145-F Van mounted telescopic platform



Iveco Daily 50C (5,200kg GVW)



LMC controls with variable outreach



Emergency lowering controls in pedestal



Knuckle/turret tail swing within the mirrors



Outriggers within the mirrors



T: 01536 721010 **E:** sales@versalift.co.uk **F:** 01536 721111 **W:** www.versalift.co.uk

«VERSALIFT» VTL-145-F

Additional Specifications

















5,200kg



Twin joystick LMC control system with LCD

Limited working area without outriggers

Optional equipment Bespoke storage racking

Walk-in or Duck-under bucket

Stabiliser controls from bucket Slew rotation interlock Reversing camera Bucket rotator (2 x 90°)***

1kV certified insulation

Chapter 8 compliance

interface screen

Diagrams



METRES

16

14





Length: 7,309cm

Height: 3,460cm

Wheelbase: 3,520cm

Key features



Manufactured from ultra-high strength steel, a profiled boom delivers exceptional rigidity, strength and smooth platform operation. For low maintenance, integrated boom wear pads now follow this profile.




Pedestal mounted emergency lowering valves, located at ground level within load area are safe and easy to access.




Impressive outreach with LMC load sensing system. A-frame outriggers and tail swing of turret within the mirrors of the vehicle for improved safety.



Optional twin joystick LMC control system enables load dependent variable outreach and up to two actions simultaneously.





Limited working area without outriggers (optional)

Notes

Technical information is subject to change without notice. Images may show optional equipment.

*Depending on the vehicle and subject to options fitted

**Max. payload after driver, passenger and fuel and subject to options fitted

***Reduced outreach

Revision: 09/2018



Versalift Distributors (UK) Ltd. 1 Altendiez Way, Latimer Park, Burton Latimer, Kettering. NN15 5YT

T: 01536 721010 E: sales@versalift.co.uk F: 01536 721111 W: www.versalift.co.uk

